



Type	Power Rating (W)	Resistance Range (Ω)		Dimensions (mm)									
		Wire Wound	Mo	L	H	W	S	H1	H2	P1	P2	P3	P4
SQZ-5	5	0.1Ω~200Ω	201Ω~50KΩ	27.0	9.5	9.5	15	24.0	9.5	4.0	2.0	7.0	1.4
SQZ-7	7	0.1Ω~200Ω	201Ω~100KΩ	35.0	9.5	9.5	22	24.0	9.5	4.0	2.0	7.0	1.4
SQZ-10	10	0.2Ω~500Ω	501Ω~100KΩ	48.0	9.5	9.5	32	24.0	9.5	4.0	2.0	7.0	1.4
SQZ-15	15	0.5Ω~600Ω	601Ω~100KΩ	48.0	12.5	12.5	32	34.5	15.0	7.0	6.0	10.0	2.7
SQZ-20	20	0.5Ω~1KΩ	1.1Ω~100KΩ	63.5	12.5	12.5	45	34.5	15.0	7.0	6.0	10.0	2.7
SQZ-30	30	0.5Ω~2KΩ	2.2Ω~100KΩ	76.0	21	19	57	35.0	7.0	7.0	6.0	10.0	2.7
SQZ-40	40	0.5Ω~2.5KΩ	2.7Ω~100KΩ	89.0	19	19	70	36.0	9.0	6.0	6.0	10.0	2.7